



**Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries**



**Date :** 07/09/2025 - 1:12 AM \*  
**EXF # :** EO-012640  
**Category :** EDGEBANDERS-OVER \$25,000  
**Brand / Model :** SCM "OLIMPIC K360"  
**Machine Type :** EDGEBANDER (W/PRE-MILLING)  
**Year of Mfg. :** 2018  
**Condition :** Good Condition  
**Elect / Voltage :** 220 V, 60 Cy, 3 Ph.  
**Special Note :**

**FOB / Region :** EASTERN CDN  
**Appr. Repl. Cost. :** \$ 73,000  
**Price :** **\$ 34,900 \***  
**Comment :** Well-maintained machine!  
**Leasing :** Lease for \$ 709/Mo. at NCL



Please ask me

**Bob Bullin**  
800-374-5009 ext. 346  
Intl. +1 704-841-2001 ext. 346  
bob.bullin@exfactory.com

\* Pricing is valid at the time of printing and subject to change at any time.

### Description :

- **SCMI OLIMPIC K 360 EDGEBANDER (W/PRE-MILLING):**

#### Specifications

- **Edge Capacity:** 0.3 to 3 mm (0.012 - 0.118"); for coiled edges: 0.3 - 6 mm Strips with 6 x 60 mm kit included; dia. coil holder plate: 780 mm (31").
- **Panel Capacity:** Min. width: 90 mm; min. length: 140 mm (3-1/2" & 5-1/2"); panel thickness min./max.: 8 - 50 mm (3/8" - 2") & max. 60 mm (2.4") with 6 x 60 mm kit included.

#### Equipped with:

- **Adjustable Infeed Fence:** Manually preset with digital indicator; pneumatic in/out positioning.

**Sales - Liquidations - Auctions - Appraisals - Consulting**

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries**

---

- **Premilling Station - RT-VP:** Spindles: (2) x 2.0 HP - 19,000 RPM; (1) PLC controlled jump action; diamond cutterheads.
- **Automatic Strip & Coil Feed Magazine:** For straight edges; 3 mm guillotine for coils.
- **Gluing Station** for EVA (Hot Melt) with: Teflon-coated glue tank; quick disconnect to change glue tanks fast if needed; Heat-up time approx. 10 Min. Includes 1.5 kg glue pot instead of standard.
- **Pressure Section:** Manual digital positioning, (3) pressure rollers: First larger; Teflon Coated and powered.

#### **Workstations**

- **End Trimming Station - K2.** Front & rear: (2) x 1/2 HP (included extra); 12,000 RPM motors mounted on THK guides; swivels 0° - 15°; rapid setup between straight & angled cutting with the automatic swivel cylinder.

Automatic positioning for (3) cutting modes: Straight, chamfered, and radius of thick edges.

- **Top & Bottom Trimming Unit - R-K.** Remote (via control panel) pneumatic positioning for (3) settings: Flush/bevel/radius trimming; (2) x 0.7 HP - 12,000 RPM motors with precision digital indicators for quick setup.
- **Top & Bottom Profile Scraping Unit.** Manual preset with: Digital indicators; large dia. copy wheels for max. accuracy; pneumatic in/out positioning.
- **Buffing Unit - SP-V:** Top/bottom; (2) x 1/4 HP - 2,800 RPM Motors; tilting up to 12°; cleaning & polishing of edges.

#### **Controls**

- **ORION - 1 Plus: Controller.** Fixed at infeed of machine; soft keys, graphics, and 4" LCD display panel.

Handles most machine setup functions & workstations; machine automation by PLC function; encoder positioned in the panel feed track pinion; diagnostics for a quick solution to many errors; process statistics

---

**Sales - Liquidations - Auctions - Appraisals - Consulting**

---

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries**

---

data: Number of pieces/edges and track feeding.

**Features & Complete with:**

- Feed speed: 36 FPM Fixed; (1) x 2.0 HP feed drive motor; 200 Hz frequency inverter for all trimming units; manual adjustable holddown pressure beam; full sound enclosure cover; outboard panel support.
- Overall dimensions: 3,600 mm (142") x 900 mm (36") x 1,600 mm (63"); approx. weight: 997 kG (2,200 Lbs).
- UL/CSA approved version.

---

**Sales - Liquidations - Auctions - Appraisals - Consulting**

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328