




Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries



Date : 04/13/2026 - 8:08 AM *
EXF # : EO-280499
Category : EDGEBANDERS-OVER \$25,000
Brand / Model : CEHISA "PRO-12 CONCEPT"
Machine Type : EDGEBANDER (W/PRE-MILL & CORNER ROUNDING)
Year of Mfg. : 2017
Condition : Good condition
Elect / Voltage : 230 V, 60 Cy, 3 Ph.
Special Note : Make Offer

FOB / Region : MIDWEST
Appr. Repl. Cost. : \$ 80,000
Price : \$ 0 *
Comment : Seller will consider all offers!
Leasing : Contact NCL for quote



Please ask me

Bob Bullin
 800-374-5009 ext. 346
 Intl. +1 704-841-2001 ext. 346
 bob.bullin@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **CEHISA PRO-12 CONCEPT ...Edgebander with Pre-Milling & Corner Rounding.**

Features:

- **Pre-Milling Station with:** 2 x1.5 Kw (2.0 HP)12,000 RPM motors, standard equipped with diamond cutters. Both spindles pneumatically controlled.
- **Automatic Edge Magazine:** for coiled material up to 3 mm thickness, strip feed magazine for up to 5 mm (3/16") solid wood banding.
- **Quick Melt Glue System, MR-5:** 10 - 15 min. heat-up time, auto temperature drop. Glue Tank is coated with nonstick material, quick-change mechanism for easy maintenance and/or color change.
- **Pressure Section:** (1) Large dia. driven and (2) idle rollers. Digital read-out and pneumatic positioning selectable from controller touch screen.

Workstations:

Sales - Liquidations - Auctions - Appraisals - Consulting



Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries

- **End Trimming Station, V-4:** Double motor front & rear, 2 x 0.35 Kw (0.5HP) - 12,000 RPM.
- **Edge Trimming Station, JC-5:** Top & bottom flush/bevel/radius trimming, 2 x 0.35 Kw (0.5 HP) - 12,000 RPM, tiltable 0° - 20°, pneumatic exclusion from operator panel.
- **Corner Rounding Unit, CR-1:** To process overhanging edges and trimming around the leading & trailing edge, 1 x 0.27 Kw (0.36HP).
- **Profile Scraping Unit, RB-8:** For thick PVC/ABS radius scraping, pneumatic in/out positioning from control panel with chip collection box.
- **Flat Glue Scraper, RR-7:** To remove potential glue squeeze-out.
- **Buffing Unit, PC-9:** Top/Bottom, 2 x 0.12 Kw (1/8HP) - 1,650 RPM motors, tilting horizontally and vertically.

Controller:

PLC Microprocessor control with color touch screen, memory up to 20 programs.

Complete With:

Feed Speed, 10 & 16 MPM (35 & 55 FPM); Power hold-down beam; Work-piece support outrigger; safety & sound enclosure.

Included Options:

Riepe, non-stick spray system; Nesting Tracer Shoes for top/bottom trimmers

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328