



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**



Date : 04/19/2024 - 12:40 PM *
EXF # : FD-010845
Category : FINISHING-SAND/DENIBBERS
Brand / Model : OPTI-SAND "L202"
Machine Type : SEALER/DENIBBER SANDER
Year of Mfg. :
Condition : Very good condition
Elect / Voltage : 230 V, 60 Cy, 3 Ph.
Special Note : Great Value

FOB / Region : MIDWEST
Appr. Repl. Cost. : \$ 25,000
Price : **\$ 10,800 ***
Comment : "Excellent" Condition machine at an "Excellent" pr
Leasing : Lease for \$ 219/Mo. at NCL



Please ask me

Dan Wolters
800-374-5009 ext. 376
Intl. +1 704-841-2001 ext. 376
dan.wolters@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **OPTI-SAND L202 Abrasive Brush Feed Through Sander;**

2-Head Abrasive Brush Sander with (1) top & (1) side heads use standard abrasive heads or cored brush loadings (not included). **11-3/4" Width and 4" height capacity.**

Specifications:

- Overhead counter-rotating arbor, 12" long arbors x 12" max. dia. sanding discs.
- Head is mounted on a height adjustable common plate with a slide assembly.
- Head tilts up to 15° and 1 HP Motor drives each arbor with inverter for variable 100 - 1,000 RPM arbor rotation speed.
- (1) Side mounted abrasive/brush head, tilt and front head adjusts in-and-out via locking hand-wheel, 6" long arbors x 8" dia. max. sanding discs.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

- 0.5 HP Motor drives each arbor with inverter for variable 100 - 1,000 RPM arbor rotation speed; all arbors are 50 mm hexagonal for positive non-slip rotation.

Feed System:

- 0" - 5" Max. part height adjustment via locking hand-wheels; 86" long fixed roller conveyor feed bed with rubber rollers,
- (2) 0.25 HP DC motor drives with variable feed speed 10 - 100 FPM
- (6) Full width overhead soft rubber pressure rollers located at infeed, outfeed and between sanding heads, rollers are connected overhead for quick height adjustments.

Includes & Features:

- Centralized control panel with digital displays and touch screen controls for spindle speed and feed rate.
- (2) 4" Dia. dust ports, min. 1,400 CFM dust collection required.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328