

## Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



**Date :** 07/13/2025 - 2:09 AM \*

**EXF #:** PM-010490

Category: PRESSES-MEM/VAC./EMBOSS

Brand / Model: WEMHONER "KT-M 15/28-240"

Machine Type: MEMBRANE VACUUM PRESS

Year of Mfg.: 1994

**Condition :** Fair Condition

Elect / Voltage: 240/480/575 V, 60 Cy, 3 Ph

Special Note:

FOB / Region: MIDWEST

Appr. Repl. Cost.: \$ 375,000

Price: \$ 0 \*

**Comment:** Older model but built to last.

**Leasing:** Contact NCL for quote

Please ask me



TCorn@exfactory.com

\* Pricing is valid at the time of printing and subject to change at any time.

## **Description:**

- WEMHONER VARIOPRESS *KT-M-15/28-240* Membrane Press with Three VacuumTrays and Storage Rack with feed/Cut. General Data: 2,800 mm x 1,500 mm (110.2" x 59.1") platen size. Press system, Hydraulic single daylight downstroke press.
- **Vacuum Tray Tables:** Approx 2,800 x 1,500 mm (110" x 59"). Three (3) tray carriage with an aluminium plate. Aluminium plate consisting of aluminium sheet with grooves and channels for aeration and lay-up frame 20 mm. Tray tables riding on profiled steel rails and arranged in a 'C' (circular) configuration.
- Total press capacity: 240 tons.. Max. chamber air pressure 6 Bar.
- **Operation:** Mechanical time of the hydraulic upstroke press for opening, closing, feeding and outfeeding. pressure build-up and reduction, not including pressing time is 45 sec. approximately.



## Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- **Technical Specifications:** Heating platen dim. 2,800 x 1,500 mm; Pressure chamber height 60 mm: Press Working height approx. 950 mm; Daylight opening Max. 250 mm (9.84"); Pressing cylinders (4) with 250 mm downstroke; Diameter of press pistons approx.125 mm; Total press pressure 2.40 kN; Operating pressure of the hydraulic system max. 320 Bar.
- **Comes With:** Free-standing Thermofoil storage/dispensing rack with feed and cut features. Vacuum pump and vacuum tank as well as valve control.
- Includes: Separate Hot-Water heating system with valve/controls and storage tank.
- Freestanding Electrical panel: With operator pushbutton controls Programmable Controller (PLC) Model SIEMENS "SIMATIC" DISPLAY and controller.
- **Construction:** Press body consisting of steel frames bolted together to form a closed unit. Each frame manufactured out of a single piece. Heated platens, top and bottom. Press can operate with or without membrane.
- Professional dismantling/rigging and Transportation available upon request.