

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date: 03/29/2024 - 1:16 AM *

EXF #: DL-010461

Category: DOVETAIL & DRAWER EQUIP.

Brand / Model: CANTEK "JDT-75"

Machine Type: DOVETAIL MACHINE

Year of Mfg.: 2024

Condition: Brand New w/Warranty

Elect / Voltage: 230 V, 60 Cy, 3 Ph.

Special Note: Brand New

FOB / Region: PACIFIC NORTHWEST

Appr. Repl. Cost.: \$ 13,650

Price: \$ 13,650 *

Comment: This CANTEK "JTD 75" is an

incredible value for a

Leasing: Lease for \$ 277/Mo. at NCL

Please ask me



800-374-5009 ext. 377 Intl. +1 704-841-2001 ext. 377

Ed.Webb@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description:

CANTEK JDT-75 Single Spindle Automatic Dovetail Machine;

Automatic Dovetailer for machining male & female dovetail (**English type**) in (2) joining drawer parts in (1) cutting cycle.

Features:

- 2 HP 21,500 RPM spindle rotation for an extremely fine finish on dovetail joints; high RPM spindle allows for precision machining of plywood & solid drawer sides.
- Independent adjustment of both the tenon and the mortise depth for precise fitting of dovetail joints.
- Dust hood for milling cutter, safety rail in front of spindle motor.
- **High quality pneumatics** for smooth feeding, resulting in quality cutting with cast iron base to ensure vibration free cutting.



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- Automatic lubrication system to spindle stroke, (3) cycle speeds for best finish results.
- Double Flute Dovetail Bit (Standard) (CANJDT75-JTCTG2T004) included

Workpiece dimensions:

- Working Length: Min. 7.87" to max. 59", working width: min. 2.36" to max. 16.93".
- Vertical material thickness: 0.275" to 2.36", Horizontal Material Thickness: 0.394" to 1.18".

Specifications:

- Fixed Pitch: 1" (25 mm).
- Spindle Speed: 21,500 RPM.
- Spindle Diameter: 0.472" (12 mm).
- Spindle Motor: 2 HP.
- Feed Motor: 2 HP.
- Feed Speeds (3): 16, 22 and 31 Cy/Min.
- Electrics: 230V/3/60 (add ...\$520.00 for 460V/3 Ph/60 Cy).
- Dimensions/Weight: 55.12" x 34.65" x 55.12" and 1,210 Lbs in weight.