




Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries



**Date :** 06/08/2026 - 8:53 PM \*  
**EXF # :** MF-012292  
**Category :** MOULDERS - FEED THROUGH  
**Brand / Model :** LEADERMAC "LMC-523S"  
**Machine Type :** MOULDER (FEED THROUGH)  
**Year of Mfg. :** 2026  
**Condition :** Brand New w/Warranty  
**Elect / Voltage :** 460 V, 60 Cy, 3 Ph.  
**Special Note :**

**FOB / Region :** PACIFIC NORTHWEST  
**Appr. Repl. Cost. :** \$ 71,000  
**Price :** \$ 0 \*  
**Comment :** LEDERMAC "LMC-523S" is a great starter machine whe  
**Leasing :** Call for Quote



Please ask me

**Torry Hiddema**  
 800-374-5009 ext. 371  
 Intl. +1 704-841-2001 ext. 371  
 torry.hiddema@exfactory.com

\* Pricing is valid at the time of printing and subject to change at any time.

**Description :**

- **LEDERMAC 523S "SMARTMAC" Feed Through Moulder;**  
 5-Head (B-R-L-T-B) with a working cap. 9" x 5".
- **Head sequence:** Bottom 7.5 HP, right/left 15 HP, top 15 HP and bottom 10 HP motor.
- Spindle dia. 40 mm with cutterhead speed of 6,000 RPM. All spindle adjustments except 1st bottom head with mechanical digital readouts.

**Features:**

- Pneumatic receding chipbreaker for top spindle and Mechanical digital readout for chipbreaker and pressure element.

**Sales - Liquidations - Auctions - Appraisals - Consulting**



**Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries**

---

- **Feed system:** Variable feed drive 20 - 80 FPM, by a 7.5 HP with Digital Speed Readout. Short stock driven feed roller at right spindle. Side pressure roller at infeed mounted to infeed table.
- Table plates, fences and chipbreaker shoes hard chromed, inside fences 32 mm height for heavy side work profiles.
- **Infeed table** 2 M (6'6") infeed straightening table, manual table lubricant pump.

**Equipped with:**

- Central lubrication system, full sound & safety enclosure, operator tools & manuals.

**Includes:**

- (1) Year warranty;
- 1st bottom with spiral Carbide cutterhead + (4) Cutterheads included, serrated back dual angle 10° / 20° with machine.
- Electrics conform to UL/CSA & CE specifications.
- (1) LMC 0026LJ Cutterhead setting stand for measuring radial diameter before and after grinding, to determine change in radial diameter

**Options:**

- Easy Setwork wich includes Schneider 5.7" HMI touch screen control and motorized adjustment of the near side and top heads and feed beam with memory for 200 profiles Add. \$ 4,295

---

**Sales - Liquidations - Auctions - Appraisals - Consulting**

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328