

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date :	04/26/2024 - 2:27 AM *
EXF # :	ML-300195
Category :	MATL. LIFT-SCISS. & HOIST
Brand / Model :	ANVER "VPF-57/20-AIR"
Machine Type :	VACUUM LIFT
Year of Mfg. :	2024
Condition :	Brand New w/Warranty
Elect / Voltage :	AIR POWERED
Special Note :	

FOB / Region :	NORTHEAST
Appr. Repl. Cost. :	\$ O
Price :	\$0*
Comment :	For lifting heavy loads up to 500 LBS.
Leasing :	Call for Quote



Please ask me

Bernie Straple 800-374-5009 ext. 339 Intl. +1 704-841-2001 ext. 339 Bernie.Straple@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description :

• ANVER VPF-57/20-AIR Generator Vacuum Lift

ANVER's latest models of vacuum generators feature high capacity pumps, valves, filters and gauges for trouble-free operation in the most demanding production environments. Designed for use with a wide assortment of vacuum lifter assemblies and interchangeable pad attachments, these high quality Vac-Packs are ruggedly built, yet affordably priced for unmatched value. The VPF-57-AIR Series features a sturdy welded frame construction for heavy weight load lifting capability.

Features:

- Air Powered Vacuum Generator.
- No electric power required, operates using dry, clean compressed air for vacuum generation. The vacuum generator is a single stage unit with no moving parts or rubber gaskets to maintain or replace.
- Takes standard dry, clean shop air. Input pressure to be regulated to 90 psi (72.5 psi on VPF-57/30-AIR). Provided with 1/4" NPT.

Sales - Liquidations - Auctions - Appraisals - Consulting



- Energy Air Saver Vacuum Generator.
- Vacuum Leakage Sensing System. The VLS is a battery powered units consisting of solid state circuitry
 with microprocessor, pressure sensor, LCD digital display in inches of Hg, and audible and visual warning
 signs (horn and red light).
- Front mounted gauges.
- Ergonomic adjustable front handlebar. Easy to grasp, large loop handlebar enables the operator to easily and safely maneuver the attached load without touching the load itself. Handlebar can be adjusted for smaller loads.
- Slide control valve with push-button safety lock.
- Vacuum check valve and reservoir

Includes:

- Anver lifting frame L150M3-110 with (3) 12" round adjustable in-line pads on 112" length beam with 1500 Lbs. capacity.
- Maximum outer pads distance 115", minimum outside pads distance 38" on a 112" Spreader Beam.
- Parking Station PS-150-3X3 assembly with mounting hardware for 3' square beams. .