



Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries



Date : 07/19/2025 - 1:29 AM *
EXF # : PD-300356
Category : PLANERS - DBL. & 4-SIDED
Brand / Model : CANTEK "GT-635ARD-16"
Machine Type : PLANER (DOUBLE SIDED)
Year of Mfg. : 2025
Condition : Brand New w/Warranty
Elect / Voltage : 460 V, 60 Cy, 3 Ph.
Special Note :

FOB / Region : WEST COAST

Appr. Repl. Cost. : \$ 44,632

Price : **\$ 43,200 ***

Comment : CANTEK ...A name you can trust and Planer that wil

Leasing : Lease for \$ 878/Mo. at NCL

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **CANTEK - GT635ARD-16 25″ Double Surface Planer**

25″ Wide x 16″ thickness capacity Add on \$2,500 for increase HP of top head to 30 HP

Features:

- Cutterheads are spiral insert types with six (6) rows of carbide inserts.
- (2) Driven and (1) idle bedroll for superior feeding of even difficult material.
- Swiveling control panel for more ergonomic access to machine controls.
- Inverter variable speed control with feed speeds from 26 to 80 FPM.



Please ask me

Louis Sicotte
800-374-5009 ext. 329
Intl. +1 704-841-2001 ext. 329
louis.sicotte@exfactory.com

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

- Easy to access external handwheel adjustment of infeed bed.
- Hard chromed worktable for high wear resistance.
- Auto lubrication to conveyor chain, central lubrication for dovetail elevation guideways.
- Sectional chip breaker and sectional feed roller before top cutterhead..
- Rubber outfeed top roller to prevent chip marking.
- Over thickness safety shut-off bar across infeed.
- Ammeter for each motor on the control panel to monitor motor load.

Specifications:

Maximum working width 25'6";

Maximum working thickness 16'6";; Minimum thickness 0.394"; Min. workpiece length 12.2'6";

Bottom head motor 20 HP, Top planing head motor 25 HP - Feed motor 5 HP

Table elevation motor 1/2 HP.

Cutterhead diameter 4", Knife dimensions 30 mm x 12 mm x 1.5 mm w/bevels (96 pcs per head)

Cutterhead speed 5400 RPM;

Feed speed (variable) 26 - 80 FPM

Dust ports 2 @ 6"; Table dimensions 27" x 103" (41.85" from the floor);

Machine voltage 460/3/60 = 70 amps.

Dims & Weight (LxWxH) 105'6" x 45.1'6" x 92.9'6"; (max.) Net weight 6700 Lbs,

Packaging dimensions 109'6" x 49'6" x 89'6"; Gross weight 7800 Lbs

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328