

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date: 07/08/2025 - 3:08 AM *

EXF #: PM-300013

Category: PRESSES-MEM/VAC./EMBOSS

Brand / Model: RIBEX "ROBO"

Machine Type: VACUUM MEMBRANE PRESS

Year of Mfg.: 2025

Condition: Brand New w/Warranty

Elect / Voltage: 230 V, 60 Cy, 3 Ph.

Special Note: Great Value

FOB / Region: MIDWEST

Appr. Repl. Cost.: \$62,500


Price: \$ 0 *

Comment: RIBEX "Robo" with PLC

Control and (100) preset pro

Leasing: Call for Quote

Please ask me



Intl. +1 704-841-2001 ext. 432

TCorn@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description:

RIBEX - ROBO, ...Vacuum Press - Available as Single or Double Table, with or without Membrane.

High End model, "new generation" RIBEX Vacuum Press Machines <u>used for 3D lamination of PVC foils to MDF</u> board.

RIBEX Vacuum Press Technology is ideal for: Doors & Panels for kitchens, bathrooms, and furniture applications.

Equipped with:

- PLC Controlled Unit with (100) Programs capacity.
- RAYTEK Digital Heating Sensors: Measures laminate not ambient temperature, Interior Cooling Fans:

Perforated metal vacuum bed allows balanced and sufficient vacuum pressure, thus providing a larger Vacuum airflow. This is a key design feature needed to maximize how the laminate conforms to the 3D shapes. - Optional (NOT included): Silicone Membrane allows the machine to laminate veneers, as well as the other laminating products to the MDF board.

Sales - Liquidations - Auctions - Appraisals - Consulting



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

Standard Specifications:

- Ergonomic body design, CE (European Norm), ISO 9001 certified products.
- Worktable safety sensors, automatic temperature control, either single or dual table control, independent vacuum, and temperature system.
- Max. temperature of 200° C (392° F); approx. operation/cycle time (4 5 nominal) minutes.

Includes:

- Thermofoil PVC unwind stand.
- BECKER U.5.100, ... Vacuum Pump: Allows 100 cbm/Hr (59 CFM), motor power of 2.2 kW (3 HP).

Dimensions & Capacity:

- Table frame dimension: 2,870 mm x 1,440 mm (112 in. x 64 in.).
- Usable area: 2,710 mm x 1,230 mm (106 in. x 48-3/8 in.); max. working thickness of 90 mm (3-1/2 in.).
- Total Power of 26.5 kW.
- Approx. weight of single table: 1,350 kG (2,970 Lbs) and double table approx. 1,800 Kg (3,960 Lbs).

Included Options:

- "ROBO" Magnetic System for support the workpiece while raising it off the worktable (PATENTED).
- Divisible table setup to use material efficiently
- Second table for "next load" preparation.
- Extra Thermo Foil PVC stand/rack.



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- Silicone membrane units installed.
- (250) Pieces ROBO Magnets (for each worktable); PVC loading magazine.
- 1-Year Warranty (excluding membrane).
- The total Machine load is 30 KW.