

# Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



**Date:** 04/25/2024 - 8:23 AM \*

**EXF #:** RC-300049

Category: CNC ROUTERS OVER \$30,000

Brand / Model: LIMTECH "ORION 510"

Machine Type: CNC ROUTER (ATC & BORING)

Year of Mfg.: 2024

**Condition:** Brand New w/Warranty

Elect / Voltage: 220 V, 60 Cy, 3 Ph.

Special Note: Special Offer

FOB / Region: WEST COAST

Appr. Repl. Cost.: \$ 126,000

Price: \$ 0 \*

Comment: A very solid 5' x 10' CNC

Router with an Industria

**Leasing:** Call for Quote

Please ask me



800-374-5009 ext. 445

Intl. +1 704-841-2001 ext. 445 norm.schust@exfactory.com

\* Pricing is valid at the time of printing and subject to change at any time.

#### **Description:**

LIMTECH ORION-510 Flat Table CNC Router with Tool Changer & Boring:

5' x 10' Capacity, great for "Nested Base Manufacturing" or just about any type of 3-Axis work.

#### Axes travel range & feed speed:

- X-Axis 61" (1,550 mm), Y-axis with 121" (3,073 mm) and Z-axis 11.8" (300 mm).
- Working Table: 61" (1,550 mm) x 121" (3,073 mm); includes (3) pop-up stops to aid in panel positioning & a manual valve controlled 6-zone special high flow vacuum table system.
- X- & Y-Axis speeds are 2,165 IPM and Z-axis is 1,000 IPM for quick traverse positioning that reduces total CNC machining time between cutting cycles.
- DELTA Servo drive powers the axes movement.

#### Machine bed/base:



# Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- The welded structurally engineered machine base provides a solid foundation for superior cut quality; the entire frame is stress relieved and heat treated.
- X-, Y- and Z-Axis travel: The moving gantry bridge travels on 1.2" (30 mm) thick hardened & precision ground rectangle linear guide slider-ways giving extra smooth movement for high speed traverse and accurate cutting.
- **Tool gantry & bridge movement** by 1" (25 mm) rack & pinion; the vertical Z-axis travels on precision ball screw for smooth consistent and highly accurate movement.

### Routing/Machining:

- (1) 12 HP (8.8 kW) Air cooled "HSD" Router spindle with: HSK Tool holders, variable programming speeds from 1,000 to 24,000 RPM.
- Tools are loaded into the "HSD" spindle by (1) 8-position, side mount on the fly tool changer carrousel.
- Tool heights can be set using the Tool Length Setting Gauge (included); machine uses ER-32 tool collets.

### **Drilling/Boring:**

• (1) 9-vertical drills spindle head in L-shape configuration for 32 mm contstruction hole & line boring.

#### **CNC Control & Operator Interface:**

- The "SYNTEC" INDUSTRY CONTROL System, gives the operator an easy to use interface and the flexibility to customize to user specifications; is Network-ready via Ethernet and with USB flash drive.
- <u>Features:</u> Canned cycle, Tool length-diameter compensation, Work Coordinates-Offsets, Spindle-Feed rate overrides, Program size up to flash drive size, DNC or drip feed operation and Unlimited offset registrations.
- Compatible with virtually all CAD/CAM programming software on the market; you choose the software that best suits your needs.

### Complete with & Includes:

 Dust hood with 6" manifold connection; (4) HSK tool holders; Tool Length Setting Gauge; MPG hand held wheel remote.



## Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- 235 CFM Dry Vacuum Pump; 7.5 kW (10 HP) Vacuum Pump with ON/OFF pre-plumbed to control pane.
- Other Features: Machine Central lubrication, Safety light beams and Automatic homing operation.
- Machine weighs approx. 8,000 Lbs; 15 CFM air consumption at 90 PSI; machine power supply is wired for 220 Volts, 60 Cy, 3-Phase.

**Includes**: Installation & Training by Factory Technician, and (1) Year Parts & Labor Warranty.