

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date: 04/25/2024 - 6:36 PM *

EXF #: RG-300021

Category: RIP SAWS - MULTI-BLADE

Brand / Model: CANTEK "MRS-175"

Machine Type: MULTI-BLADE RIP SAW (DIP CHAIN)

Year of Mfg.: 2024

Condition: Brand New w/Warranty

Elect / Voltage :

Special Note:

FOB / Region: PACIFIC NORTHWEST

Appr. Repl. Cost.: \$0

Price: \$61,700 *

Comment: Look at that DEPTH OF

CUT!!!!

Leasing: Lease for \$ 1,240/Mo. at

NCL

Please ask me



800-374-5009 ext. 348 Intl. +1 704-841-2001 ext. 348

joe.retzlaff@exfactory.com

Description:

- CANTEK MODEL MRS-175 6.9" THICK CUTTING HEAVY-DUTY GANG RIPSAW:
- FEATURES:
- Massive cast iron base provides incredible absorption characteristics for high quality deep cutting operations
- Precision chain and rails (dip chain) system facilitates straight line cutting
- Equipped with a blade mist cooling device providing cooling and cleaning for sawblades during cutting increasing blade life and improved cut quality.

^{*} Pricing is valid at the time of printing and subject to change at any time.



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- Motorized saw arbor and thickness adjustment for operator convenience.
- Specially designed auxiliary powered outfeed roller assures maximum smoothness of workpiece outfeed especially when working on extra thick, heavy and moist wood.
- A digitally controller lubrication unit is provided to provide consistent oil protection to the feed chain and guide rails. If the oil level drops below a safe level a warning lamp will light up and the feed chain will stop automatically.
- Equipped with an electronic amperage display which is tied in to an overload protection where if the saw motor exceeds a rated amperage the feed chain slows down automatically. This prevents the potential damaged to the saw arbor and/or blades and also prolongs blade life up to 20%.
- Variable feed speed adjustment by frequency inverter from the front of the machine.
- · Please note. with safety cover non-CE
- Measurement: 255x210x170(cm) N.W./G.W.:3,150KGS/3,350KGS

SPECIFICATIONS

- Max. cutting thickness, 6.9"
- Max. cutting width, 13-3/4"
- Fixed inside blade to column, 14.9"



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- Min. working length, 27-1/2"
- Max. saw blade diameter, 14" to 18"
- Sawblade bore, 70 mm or 90mm double keyed
- Saw arbor diameter, 70 mm without sleeve 90mm with sleeve
- Saw arbor speed, 2500 RPM
- Saw arbor motor, 75 HP (100 HP optional)
- Saw arbor elevation motor, 1/2 HP
- Feed motor, 3 HP (5HP optional)
- Variable feed speed, 8 80 FPM (higher speed optional)
- Powered raise & lower of rolls, 1/2 HP
- Dust hood dia., 8"
- Table height (pass line), 29.3"
- Electrics to UL/CSA standards 230/460 or 575-volt, 3-phase, 60-cycle



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

	•	Table area	(L x W),	72.4" x 31.1	1"
--	---	------------	----------	--------------	----

•	Overall dimensions	(L x W x H), 95	.5" x 90.5" x 63"	, Net weight 6,600 lbs.
---	--------------------	-----------------	-------------------	-------------------------